



# KANOMAX

The Ultimate Measurements

ISO9001 ISO14001



JQA2790



JQA-EM1628

# Indoor Air Quality Monitor IQM 60



## Features


- Multiple Gas Sensors (up to six)
- Analytic GSS Technology / PID / NDIR
- Temperature and Humidity Sensors
- Particulate Monitor (option)
- Rapid Real-time Data Sampling
- Min / Max / Average Sampling
- RS 232C / USB Communication
- Wireless Communication (optional)
- PC Data Logging Software

## Applications

- Indoor Air Quality Investigation
- Industrial Hygiene Quality Control
- Occupational Health Control

## Benefits

- Multi-Parameter Measurement - Gas, temp, humidity, particle
- Large Internal Data Storage Capacity
- User Defined Calibration
- Low Maintenance Cost
- Portable unit



# Most IAQ Parameters Covered in This Single Unit

## ■ Applications



U.S. Green Building Council  
LEED Certification



Indoor Air Quality Investigation



Detect Sick Building Syndrome

# Indoor Air Quality Monitor IQM 60

## Specifications

Gas Sensor Modules	Sensor	Range (ppm)	Lowest detection	Accuracy	Precision	Resolution
Carbon dioxide	NDIR	0 - 2,000	6 ppm	<40 ppm + 3%	6 ppm	1 ppm
Carbon dioxide	NDIR	0 - 5000	6 ppm	<150 ppm + 5%	6 ppm	1 ppm
Carbon monoxide	GSS	0 - 100	0.5 ppm	<+/- 5 ppm	1 ppm	0.1 ppm
VOC isobutylene	GSS	0 - 25	0.1 ppm	<+/- 10%	0.2 ppm	0.1 ppm
VOC isobutylene	PID	0 - 20	10 ppb	<10%	0.02 ppm	0.01 ppm
Non-methane hydrocarbon	GSS	0 - 25	0.1 ppm	<+/- 0.5 ppm	0.2 ppm	0.1 ppm
Hydrogen sulphide	GSS	0 - 10	10 ppb	<+/- 0.5 ppm	0.02 ppm	0.01 ppm
Nitrogen dioxide	GSS	0 - 0.200	10 ppb	<+/- 15%	0.005 ppm	0.001 ppm
Ozone	GSS	0 - 0.150	1 ppb	<+/- 0.005 ppm	0.002 ppm	0.001 ppm
Ozone	GSS	0 - 0.500	1 ppb	<+/- 0.008 ppm	0.004 ppm	0.001 ppm

\* Other parameters available

Temperature / Humidity Sensor	Range	Accuracy	Resolution
Temperature	-20 - 100C	+/- 0.3C @ 25C	0.1C
Humidity	0 - 100%RH	+/- 2%RH @ 25C	0.1%RH
<b>Particle Monitor (optional)</b>	Range	1 - 2000 $\mu$ g/m	
	Particle Size	0.1 - 100 $\mu$ m	
	Precision	3 $\mu$ g/m	
	Accuracy	8% NIOSH 0600	
	Stability	5% of reading	
	Cut Points	TSP, PM1, PM2.5, PM10	

Interface	RS232 (Serial cable and USB adapter supplied)
Data Storage	Removable 1GB SD card
Wireless Communication (optional)	GSM modem
Power Supply	AC adapter / External Li-ion portable power station (optional)
Enclosure	Aluminum and powder coated steel
Dimensions	W 10.9 x D 9.3 x H 5.2 inches (278 x 236 x 132 mm)
Weight	Approx. 11 lb (5.0 kg)
Standard Accessories	Operation Manual, Standard Sensors (CO, CO <sub>2</sub> , Temperature, R/H), AC Adapter, PC Configuration and Data Logging Software
Optional Accessories	TSP Particulate Monitor, PM2.5 Cyclone, PM10 Cyclone, Replacement PID Lamp
Optional Sensor Module	<ul style="list-style-type: none"> <li>• VOC isobutylene sensor module</li> <li>• PID isobutylene sensor module</li> <li>• Ozone sensor module</li> <li>• Nitrogen dioxide sensor module</li> <li>• Non Methane Hydrocarbon sensor module</li> <li>• Hydrogen sulphide sensor module</li> <li>• Ammonia sensor module</li> </ul>

\* Specifications subject to change without prior notice



Distributed by:

### Kanomax USA, Inc.

P.O. Box 372

219 US Hwy. 206, Andover, NJ 07821 U.S.A.

TEL: 1-800-247-8887 (USA) • 1-973-786-6386

FAX: 1-973-786-7586

E-mail: info@kanomax-usa.com

URL: www.kanomax-usa.com