

DUCT AIR LEAKAGE TESTER *DALT 6900*

Automated commercial duct air leakage testing

Kanomax introduces a new Duct Air Leakage Tester (DALT) for commercial duct systems. The instrument provides step-by-step test configuration and automated leakage testing based on the SMACNA HVAC Air Duct Leakage Test Manual. The instrument is designed for easy transport to the job with a small footprint and stair walker dolly.

DUCT LEAKAGE TESTER SPECIFICATIONS			
Duct static pressure range	+/- 10 in. w.g. (+/- 2500 Pa)		
Volumetric flow range	2 to 377 CFM (4 to 640 m3/h)		
Testing surface area (at 4 in.w.g.)	Up to 10500 sq. ft.		
Temperature range	-4 to 140 °F (-20 to 60 °C)		
Weight	165 lbs. (75kg)		

^{*}Specifications are subject to change without notice..



FEATURES AND BENEFITS

- Step-by-step test configuration and automated leakage testing based on the SMACNA Test Manual.
- Automatically calculates leakage percent per AABC standards.
- Capable of both positive and negative duct leakage tests.
- Easy transport to the job with a small footprint.
- Option to connect two DALTs for bigger projects.

< Home	0000/1000		13:30
Tool: Grid	0	008262)
Standard:	υ.	000202	cfm/ft2
SMACNA	Lim	it 0.049246	
Class: 02	Pass		
Area:			
5000.0 ft2	70.2 °F	29.9 inHg	4.000 inH2O
BACK START SAVE			

KANOMAX USA, INC. 219 US HWY 206, ANDOVER, NJ 07821 USA

TEL: 973-786-6386 **FAX:** 973-786-7586

E-MAIL: SALES@KANOMAX-USA.COM URL: WWW.KANOMAX-USA.COM

DISTRIBUTED BY: